








V-Count Hardware Technical Specifications

							
	V-Count 3D Mini+	V-Count Queue Mini	V-Count 3D Alpha+	V-Count MultiCamera Heatmap	V-Count Staff Exclusion	V-Count Queue	V-Count Demographic Analysis
Device Dimensions	(Rectangular Cover): 127 x 127 x 38 mm	(Rectangular Cover): 127 x 127 x 38 mm	(Rectangular Cover): 225 x 70 x 40 mm	(Rectangular Cover): 127 x 127 x 38 mm	(Rectangular Cover): 127 x 127 x 38 mm	(Rectangular Cover): 225 x 70 x 40 mm	(Rectangular Cover): 127 x 127 x 38 mm
Packing Dimensions (WxDxH)	250 x 167 x 82 mm	250 x 167 x 82 mm	257 x 224 x 91 mm	250 x 167 x 82 mm	250 x 167 x 82 mm	257 x 224 x 91 mm	250 x 167 x 82 mm
Device Weight	236g	236g	382g	236g	218g	382g	236g
Package Weight	1186g	1186g	1404g	1202g	1184g	1404g	1202g
Installation Height	Min. Height 2.2m, Max. Height: 2.8m	Min. Height 2.2m, Max. Height: 2.8m	Min. Height 2.8m, Max Height 9m	Min. Height 2.5m, Max. Height 6m	70m Diameter(Theoretically)	Min. Height 2.8m, Max Height 9m	Min. Height 1m, Max. Height 3m
Data Transfer	PoE: IEEE802.3af (48 V DC)						
Adaptor	5V 3A						
Power Consumption	15W						
Monthly Data Usage(Avg)	18.29MB	122MB**	18.29MB	1.91GB***	102MB****	122MB**	917MB****
Peak Usage at Calibration Process	Max 2GB/month	Max 2GB/month	Max 2GB/month	Max 3GB/month	Max 2GB/month	Max 2GB/month	Max 2GB/month
Interface	HTTP / HTTPS						
Operating System	Linux based Vcount OS						
Time	NTP, Adjustable Timezone, Automatic Daylight Saving Adjustments						
Ethernet Connection	Yes						
Data Storage	20 Years offline storage with auto synchronization		3 Months offline storage with auto synchronization		10 Years offline storage with auto synchronization		10 Years offline storage with auto synchronization
Minimum Lux	30		-		-		30
User Levels	3 Levels: Admin, Standard, Guest User						
Cabling	Cat5 - Cat6						
Environmental Specs	Operating Env: Temperature: -15 °C to 40 °C, Humidity: 10% to 90% Storage Env: Temperature: -40 °C to 70 °C, Humidity: 10% to 95%						
Max Ethernet Cable Length	90m						

V-Count 3D Mini+			V-Count 3D Alpha+				V-Count MultiCamera Heatmap		V-Count Queue				
HEIGHT (CM)	LENS(mm)		LENS(mm)				HEIGHT (CM)	Coverage Area	LENS(mm)				
	2.1	3.6	2.1	3.6	6.0	8.0			2.1	3.6	6.0	8.0	
240	130	130	240	285	-	-	240	10m x 7.2m	72 m ²	240	285	-	-
250	225	225	360	330	-	-	260	10.5m x 7.5m	78.75 m ²	300	330	-	-
260	240	240	390	390	-	-	280	11m x 8m	88 m ²	330	390	-	-
280	285	285	360	420	220	-	300	12m x 8.4 m	100.8 m ²	360	420	220	-
300	-	-	390	480	260	-	330	12m x 8.4 m	100.8 m ²	390	480	260	-
330	-	-	420	-	270	-	360	12.5m x 9m	112.5 m ²	420	-	270	-
360	-	-	450	-	330	-	390	12.5m x 9m	112.5 m ²	450	-	330	-
390	-	-	500	-	390	220	420	13m x 9.5m	123.5 m ²	500	-	390	220
420	-	-	520	-	440	240	450	13m x 9.5m	123.5 m ²	520	-	440	240
450	-	-	550	-	455	255	500	13m x 9.5m	123.5 m ²	550	-	455	255
500	-	-	600	-	585	285	540	13m x 9.5m	123.5 m ²	600	-	585	285
520	-	-	650	-	610	225	560	13m x 9.5m	123.5 m ²	650	-	610	225
550	-	-	700	-	635	240	600	13m x 9.5m	123.5 m ²	700	-	635	240
600	-	-	740	-	655	255	-	-	-	740	-	655	255
650	-	-	800	-	680	280	-	-	-	800	-	680	280
700	-	-	900	-	735	335	-	-	-	900	-	735	335
750	-	-	-	-	-	-	-	-	-	-	-	-	-
800	-	-	-	-	-	-	-	-	-	-	-	-	-
900	-	-	-	-	-	-	-	-	-	-	-	-	-

** Calculated for 16 people waiting in Queue
 *** Calculated for 50 people waited for 2 minutes
 **** Calculated for 50 BE Devices detected
 ***** Calculated for 64 Faces per period

* PoE: V-Count hardware is also compatible with PoE Injectors and PoE Switches. Please find the link for suggested PoE Injectors/Switch and Router below. The devices only work with units that have these technical specifications. Can be bought separately.

- [PLANET-PXE-16](#)
- [NETGEAR GS728TTPP - 28PT GLE-POE+ SMART SWITCH](#)
- [ASUS RT-AL12](#)
- [ZYXEL GS1300-S10P](#)
- [PLANET-WG528-10000P](#)
- [PLANET-GS-4210-8P2T2S](#)
- [NETGEAR-GS5301P](#)

Data transfer rates apply after the calibration is finalized.

www.v-count.com
sales@v-count.com

USA: 429 Lenox Avenue, Miami Beach, FL 33139 USA | Tel: +1 786 446 7276
 London Office: TIC, 2-101, 33 Queen St, London EC4B 1AQ, United Kingdom | Tel: +44 203 917 4649
 Middle East Office: One Central The Offices | 01.03 Po Box 9821 Dubai World Trade Center Dubai, UAE | +971 52 383 111
 Europe Office: İstiklal Caddesi Msır Apt. No: 163 D:20 34433 Tomtom Mah. Beyoğlu, İstanbul, Turkey. | Tel: +90 850 840 4646

